



A **REDMOND** COMPANY

SAFETY DATA SHEET

Product Code: AB3A005 (BENTONITE) Updated: 10/19/16

SURETECH 80

Natural Unaltered High Swelling Sodium Bentonite

Description

SURETECH 80 is a 100% all natural unaltered high swelling sodium bentonite. SURETECH's ultra low permeability makes it a preferred choice for all your Civil and Environmental Engineering containment and sealing applications.

Application

- Soil Sealant
- Reservoirs
- Municipal Landfills
- · Sanitation Lagoons
- Hazardous Storage
- Tailings Ponds
- · Leach Pads
- Canals
- · Tank Farms

Typical Properties

Product Description

Color Density рΗ Swell Moisture

Typical SURETECH 80

Tan to Brownish Red 66 lbs/ft3 (compact) 8.5 to 9.0 1200% 8 to 13 wt.%

-	•						•	•
	ie١		Δ	n	2	I۱	CI	ıc
_	-	<i>'</i> –	\boldsymbol{n}		a	ιv	J.	ıa

SCREEN MESH	PERCENT	SCREEN MESH	PERCENT
+50 Mesh	Trace	+200 Mesh	25.0%
+100 Mesh	5.0%	-200 Mesh	75.0%

Advantages

- · 100% Natural
- Ultra Low Permeability Barrier
- Wide range of use

- · Great Containment Barrier
- Mixes quickly and easily
- Excellent hard water performance

Mixing

The percent of SURETECH 80 used should be determined through permeability testing and user specification requirements.

Packaging

SURETECH 80 is packaged in 3000 lb. sacks or bulk.

Availability

To order SURETECH 80 please contact us at:

Western Clay Company

PO BOX 127 Aurora, Utah 84620 Phone: 435-529-3281 Toll Free: 800-982-7960

Fax: 435-529-3714